



Handlauf Ø 42,4 mm

AISI304 / V2A=02

AISI316 / V4A=04

			Ø	L	Glasstärke	€/St.	€/St.
2042.1250.	02	04	42,4	1250	8,0 – 21,5 mm		
2042.2500.	02	04	42,4	2500	8,0 – 21,5 mm		
2042.5000.	02	04	42,4	5000	8,00 – 21,5 mm		



Gummiprofil

		Glas T	L	€/St.
2042.0811.	00	8,0 – 11,0	2500	
2042.1214.	00	11,5 – 13,5	2500	
2042.1618.	00	16,0 – 17,5	2500	
2042.2122.	00	20,0 – 21,5	2500	



Steckfitting 90°, Eckig

AISI304 / V2A=02

AISI316 / V4A=04

			Ø	Glasstärke	€/St.	€/St.
2042.0003.	02	04	42,4	8,0 – 21,5 mm		



Steckfitting 90° Eckig horizontal

AISI304 / V2A=02

AISI316 / V4A=04

			Ø	Glasstärke	€/St.
2042.0004.	02		42,4	8,0 – 21,5 mm	



Steckfitting 90°, Verbinder

AISI304 / V2A=02

AISI316 / V4A=04

			Ø	Glasstärke	€/St.	€/St.
2042.0006.	02	04	42,4	8,0 – 21,5 mm		



Wandflansch

AISI304 / V2A=02

AISI316 / V4A=04

			Ø	Glasstärke	€/St.
2042.0005.	02		42,4	8,0 – 21,5 mm	



Abschlussstopfen

AISI304 / V2A=02

AISI316 / V4A=04

			Ø	Glasstärke	€/St.	€/St.
2042.0002.	02	04	42,4	8,0 – 21,5 mm		